

**A RESOLUTION TO AUTHORIZE THE REPAIRS TO THE PARKING BAY FLOOR AT
THE COMBINED SERVICE FACILITY (PHASE I)**

NOW, THEREFORE, BE IT RESOLVED by the Mayor and the City Council of the City of Rolling Meadows, Illinois, that the proposal submitted by Artlow, located at 170 Gary Avenue, Carol Stream, IL 60188, in the amount of \$40,000, for the repairs to the parking be accepted. Funding is to be derived from Building & Land Fund (33) in Fiscal Year 2012 budget, with reimbursement by the Rolling Meadows Park District at 34.7% of the entire project cost; the net project cost to the City of Rolling Meadows is \$29,018.

YEAS:

NAYS:

ABSENT:

Passed and approved this 27th day of March, 2012.

Tom Rooney, Mayor

ATTEST:

Ginny Cotugno, Deputy City Clerk

Project Photographs



Parking Bay Floor Delaminating


PROPOSAL FOR CITY OF ROLLING MEADOWS
HEAVY DUTY EPOXY CONCRETE FLOOR RESURFACING PROJECT

Honorable Mayor and City Council

Rolling Meadows, IL

The undersigned having examined the specifications and all conditions affecting the work propose to provide to the City of Rolling Meadows for the LUMP SUM PRICING for the installation of a Heavy Duty Troweled Epoxy Concrete Floor Resurfacer With a High Durability Coating contract as detailed in the attached specifications.	\$ 57,644.00
--	---------------------

Liner Foot Price for up to 1,000 liner feet by 4" wide Safety Yellow color additive for vehicle parking lines for approximately 18 -20 parking stalls and or walkway delineation.	\$ 2.65
	<i>Liner Foot Price</i>

Product Manufacture being proposed:	SIKA
Product Name being proposed:	SIKAFLOOR #110
Company Name:	ARTLOW SYSTEMS, INC.
Signed By:	
Print Name:	RANDALL S. RICHTER
Title:	PRESIDENT
Address:	170 S. GARY AVENUE - CAROL STREAM, IL 60188-2018
Federal Tax ID Number:	36-2756469
Telephone:	(630) 653-8111
Cell Phone:	(630) 774-5854
Email Address:	bsimpson@artlow.com
Date:	3/19/2012

The successful bidder and all subcontractors shall provide the City of Rolling Meadows and Rolling Meadows Park District a Certificate of Insurance naming the City of Rolling Meadows as additional insured for the purposes of this contract. **This quote shall be honored for ninety (90) days from date of bid opening.** In all cases the "OR EQUIVALENT" clause shall apply. The acceptance or rejection of any option shall be at the sole discretion of the City of Rolling Meadows. Any and all deviations or exceptions to the specifications MUST be listed. The City of Rolling Meadows reserves the right to accept or reject any or all bids and to waive any or all technicalities. By signing this proposal page the bidder agrees to provide all items in the enclosed bid as specified. **Acceptance or Rejection of any Option shall be at the sole discretion the City of Rolling Meadows.**

Limitations

- Minimum/Maximum substrate temperature: 60°F/85°F (15.5°C/30°C).
- Maximum relative humidity: 85%.
- Substrate temperature must be at least 5°F (3°C) above measured dew point.
- Conduct quantitative anhydrous calcium chloride testing in accordance with ASTM-F1869. Maximum acceptable test result is 3 pounds per 1,000 ft² per 24 hours. Determine the surface moisture content by using an impedance moisture meter designed for use on concrete as detailed in ASTM E-1907. Acceptable test results shall be 4% by mass or less. If over, use Sikafloor EpoCem 81/82 or Sikafloor Vapor Block.
- Do not use on exterior, on-grade substrates.
- Terminate at shoulders cut into substrate, avoid feather-edging.
- Freshly applied Sikafloor 105 should be protected from dampness, condensation and water for at least 24 hrs.
- Do not thin this product. Addition of thinners will slow the cure and reduce the ultimate properties of this product. Critical recoat times will also be affected.
- This product is not designed for exterior use, immersion, or any use where moisture can reach the underside of the resurfacer.
- Will discolor over time when exposed to sunlight (UV) and under certain artificial lighting conditions. UV resistant, light stable topcoats are available where ultimate color/clarity retention is required.

Caution

COMPONENT R: WARNING - IRRITANT, SENSITIZER: Contains epoxy resins, Furfuryl Alcohol (CAS 98-00-0). Eye irritant. May cause skin/respiratory irritation. Prolonged and/or repeated contact with skin may cause allergic reaction/sensitization. Deliberate concentration of vapors for purposes of inhalation is harmful and can be fatal. Harmful if swallowed. **Strictly follow all use, handling and storage instructions.**

COMPONENT H: WARNING: CORROSIVE, SENSITIZER, IRRITANT. Contains amines (mixture), bisphenol A (CAS 80-05-7). Contact with skin and eyes causes severe burns. Respiratory irritant. May cause eye/skin irritation. Possible skin sensitization/allergic reaction with prolonged or repeated exposure. Harmful if swallowed. Deliberate concentration of vapors for purposes of inhalation is harmful and can be fatal. **Strictly follow all handling, use and storage instructions.**

First Aid

Eyes – Hold eyelids apart and flush thoroughly with water for 15 minutes. **Skin** – Remove contaminated clothing. Wash skin thoroughly for 15 minutes with soap and water. **Inhalation** – Remove to fresh air. **Ingestion** – Do not induce vomiting. Dilute with water. **Contact physician. In all cases contact a physician immediately if symptoms persist.**

Handling and Storage

Wear protective equipment (gloves/safety glasses/clothing) to prevent contact with skin and eyes. Keep container closed in a cool dry place. Wash skin thoroughly with soap and water after use. Use with adequate, general and local, exhaust ventilation. In absence of adequate ventilation, use a properly fitted NIOSH respirator. Remove contaminated clothing. Launder before reuse. Store in cool dry well ventilated area with container closed.

Clean Up

Avoid direct contact with eyes and skin. Wearing chemical resistant goggles/gloves/clothing, collect spill. Ventilate area. In absence of adequate ventilation, use properly fitted NIOSH respirator. Sweep up spill and place in closed container. Dispose of in accordance with applicable local, state and federal environmental regulations.

Additional Info

Technical Data Sheets are updated periodically. To ensure the most current version is being used, visit Technical Resources on www.sikafloorusa.com. Proper material application is the responsibility of the user. Site visits made by Sika personnel are for making technical recommendations only and not for supervising or providing quality control. Before applying for protection against specific chemical environments, consult Chemical Resistance Guide or Sika Technical Service.

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at www.sikacorp.com or by calling 800-933-7452.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available online at www.sikaconstruction.com or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKASHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKASHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Visit our website at www.sikaconstruction.com

1-800-933-SIKA NATIONWIDE

Regional Information and Sales Centers. For the location of your nearest Sika sales office, contact your regional center.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225

Sika Canada Inc.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



ISO 9000:2000

